Armadi di sicurezza

Armadi Ignifughi

ARMADI IGNIFUGHI PER PROTEZIONE DOCUMENTI E SUPPORTI MAGNETICI CON COMBINAZIONE ELETTRONICA DIGITALE

Caratteristiche tecniche:

- Alta protezione contro il fuoco: resistenza di 90 o 120 min. secondo il modello in condizioni di esposizione al fuoco, ad una temperatura di 1010°C circa.
- L'armadio è dotato di una serratura elettronica con milioni di combinazioni possibili.
- Scompartimenti specifici per documenti cartacei e supporti magnetici.
- N. 1 ripiano regolabile.
- Cassa interna supplementare costituita da pannelli di materiale melaminico e da specifiche protezioni che hanno funzione di isolante termico per la salvaguardia dei supporti magnetici. Protezione contro i campi magnetici ed i fenomeni elettrostatici.
- Catenacci fissi sulla porta (lato cerniere) che impediscono lo smontaggio della stessa in caso di tentativo d'apertura tramite forzatura delle cerniere e con funzione "antistrappo".
- Il modello 120 è provvisto di ruote e profili copriruote.

Armadi per protezione documenti e supporti magnetici con combinazione elettronica digitale								
Modello	Dimensioni esterne (mm)			Dimensioni interne (mm)			Peso (kg)	Resistenza al fuoco (min.)
	H	L	P	H	L	P		
AIDM0080 E	831	520	520	486	380	300	130	120
Scompartimento Supporti Magnetici				104	227	231		90
AIDM0120 E	1220	655	560	542	475	350	250	120
Scompartimento Supporti Magnetici				339	372	251		90

Capacità interna supporti magnetici						
Modello	4mm DAT	8mm AIT	CD	DLT	LTO/Ultrium	3590Cartridge
AIDM0080 E	64	34	20	12	24	8
AIDM0120 E	396	186	108	72	111	74

ARMADI IGNIFUGHI PER PROTEZIONE DOCUMENTI

Caratteristiche tecniche:

- Alta protezione contro il fuoco: resistenza da 60 min. a 120 min., secondo il modello, in condizioni di esposizione al fuoco ad una temperatura di 1010°C.
- Catenacci fissi sulla porta (lato cerniere), che impediscono lo smontaggio della stessa in caso di tentativo d'apertura tramite forzatura delle cerniere e con funzione "antistrappo".

Disponibile in due versioni:

- Serratura ad alta sicurezza certificata EN 1300, con chiave a doppia mappa.
- Serratura elettronica con milioni di combinazioni possibili e alimentazione con batterie alcaline esterne
- Internamente attrezzati con ripiani e cassetto.
- I modelli 50 e 80 sono dotati di piedini in gomma e di 2 fori di fissaggio sullo schienale.
- I modelli 150, 355 e 635 sono dotati di ruote e profili copriruote.
  Per il fissaggio sono previsti 2 fori sullo schienale.

Armadi per protezione documenti								
Modello	Dimensioni esterne (mm)			Dimensioni interne (mm)			Peso (kg)	Resistenza al fuoco (min.)
	H	L	P	H	L	P		
AIPD0050 K/E	546	450	460	430	350	328	65	60
AIPD0080 K/E	832	520	520	676	380	330	120	90
AIPD0150 K/E	1220	655	560	980	475	350	230	120
AIPD0355 K/E	1690	775	650	1450	595	440	390	120
AIPD0635 K/E*	1745	1116	700	1505	946	490	550	120

** Versione con 2 battenti*

ARMADI IGNIFUGHI PER SUPPORTI MAGNETICI

Caratteristiche tecniche:

- Alta protezione contro il fuoco: resistenza da 60 min. a 90 min., secondo il modello, in condizioni di esposizione al fuoco ad una temperatura di 1010°C.
- Cassa interna supplementare costituita da pannelli di materiale melaminico e da specifiche protezioni che hanno funzione di isolante termico.
- Le guarnizioni della cassa interna e le scanalature della porta esterna assicurano la tenuta ermetica a liquidi, aria, vapore e fumo.

Disponibile in due versioni:

- Serratura ad alta sicurezza certificata EN 1300, con chiave a doppia mappa.
- Serratura elettronica con milioni di combinazioni possibili.
- Protezione contro i campi magnetici ed i fenomeni elettrostatici.
- N. 1 ripiano regolabile.
- Tutti i modelli sono dotati di piedini in gomma.

Armadi ignifughi per supporti magnetici								
Modello	Dimensioni esterne (mm)			Dimensioni interne (mm)			Peso (kg)	Resistenza al fuoco (min.)
	H	L	P	H	L	P		
AISM0125 K/E	420	352	433	224	157	206	45	60
AISM0530 K/E	522	404	440	314	197	201	65	60
AISM0070 K/E	695	500	500	419	277	231	120	90

Capacità interna						
Modello	4mm DAT	8mm AIT	CD	DLT	LTO/Ultrium	3590Cartridge
AISM0125	74	33	30	16	22	12
AISM0530	150	54	53	20	36	22
AISM0070	312	168	111	62	96	64

ARMADI IGNIFUGHI PER SUPPORTI MAGNETICI

Caratteristiche tecniche:

- Alta protezione contro il fuoco: resistenza di 120 min. in condizioni di esposizione al fuoco ad una temperatura di 1010°C.
- Cassa interna supplementare costituita da pannelli di materiale melaminico e da specifiche protezioni che hanno funzione di isolante termico.
- Le guarnizioni della cassa interna e le scanalature della porta esterna assicurano la tenuta ermetica a liquidi, aria, vapore e fumo.
- Protezione contro i campi magnetici ed i fenomeni elettrostatici.

Disponibile in due versioni:

- Serratura ad alta sicurezza certificata EN 1300, con chiave a doppia mappa.
- Serratura elettronica con milioni di combinazioni possibili.
- Cassetti interni estraibili su guide telescopiche provvisti di divisori interni regolabili.
- Ripiani interni regolabili.
- Ruote e profili copriruote.

Armadi ignifughi per supporti magnetici								
Modello	Dimensioni esterne (mm)			Dimensioni interne (mm)			Peso (kg)	Resistenza al fuoco (min.)
	H	L	P	H	L	P		
AISM0825 K/E	830	690	720	489	402	406	260	120
AISM0120 K/E	1220	690	720	879	402	406	350	120
AISM0130 K/E	1445	690	720	1104	402	406	480	120
AISM0635* K/E	1745	1200	720	1404	402x2	406	760	120

** Versione con 2 battenti*

Capacità interna						
Modello	4mm DAT	8mm AIT	CD	DLT	LTO/Ultrium	3590Cartridge
AISM0825	232	114	188	84	114	96
AISM0120	464	228	376	168	228	192
AISM0130	580	285	470	225	285	240
AISM0635	1160	570	940	420	570	480

Safety cabinets

Fire-resistant cabinets

FIRE-RESISTANT CABINETS TO PROTECT DOCUMENTS AND MAGNETIC STORAGE MEDIA WITH DIGITAL ELECTRONIC COMBINATION

Technical features:

- High fire protection: 90- or 120-minute resistance, according to the model in fire exposure conditions, at a temperature of about 1010°C.
- The cabinet is provided with an electronic lock with millions of possible combinations.
- Specific compartments for paper documents or magnetic storage media.
- N. 1 adjustable shelf.
- Additional internal safe, made up of melamine panels and of specific protections, with thermal insulating function for the security of the magnetic storage media. Protection against magnetic fields and electrostatic phenomena.
- Fixed lock bolts on the door (hinges side), impeding the disassembly of the same, in case of unlocking attempt by forcing the hinges and with “anti-tear” function.
- The 120 model is provided with wheels and wheel-covering profiles.

Fire-resistant cabinets to protect documents and magnetic storage media with digital electronic combination								
Model	External sizes (mm)			Internal sizes (mm)			Weight (kg)	Fire resistance (mins.)
	H	L	P	H	L	P		
AIDM0080 E	831	520	520	486	380	300	130	120
Compartment for Magnetic Storage Media				104	227	231		90
AIDM0120 E	1220	655	560	542	475	350	250	120
Compartment for Magnetic Storage Media				339	372	251		90

Internal capacity of compartment for magnetic storage media						
Model	4mm DAT	8mm AIT	CD	DLT	LTO/Ultrium	3590Cartridge
AIDM0080 E	64	34	20	12	24	8
AIDM0120 E	396	186	108	72	111	74

FIRE-RESISTANT CABINETS FOR DOCUMENT PROTECTION

Technical features:

- High fire protection: 60- or 120-minute resistance, according to the model in fire exposure conditions, at a temperature of about 1010°C.
- Fixed lock bolts on the door (hinges side), impeding the disassembly of the same, in case of unlocking attempt by forcing the hinges and with “anti-tear” function.

Available in two versions:

- High security EN 1300 certified lock, with dual key
- Electronic lock with millions of possible combinations and powered by external alkaline batteries
- Equipped inside with shelves and drawer
- Models 50 and 80 are provided with rubber feet and 2 fastening holes on the back
- Models 150, 355 e 635 are provided with wheels and wheel-covering profiles.
  2 holes are provided on the back for fastening

Armadi per protezione documenti								
Model	External sizes (mm)			Internal sizes (mm)			Weight (kg)	Fire resistance (mins.)
	H	L	P	H	L	P		
AIPD0050 K/E	546	450	460	430	350	328	65	60
AIPD0080 K/E	832	520	520	676	380	330	120	90
AIPD0150 K/E	1220	655	560	980	475	350	230	120
AIPD0355 K/E	1690	775	650	1450	595	440	390	120
AIPD0635 K/E*	1745	1116	700	1505	946	490	550	120

** 2-door version*

FIRE-RESISTANT CABINETS FOR MAGNETIC STORAGE MEDIA

Technical features:

- High fire protection: 60- or 120-minute resistance, according to the model in fire exposure conditions, at a temperature of about 1010°C
- Additional internal safe, made of melamine panels and of specific protections, with thermal insulating function
- The seals of the internal safe and the grooves of the external door assure tightness to liquids, air, vapour and smoke

Available in two versions:

- High security EN 1300 certified lock, with dual key.
- Electronic lock with millions of possible combinations.
- Protection against magnetic fields and electrostatic phenomena.
- N. 1 adjustable shelf.
- All the models are provided with rubber feet.

Fire-resistant cabinets for magnetic storage media								
Model	External sizes (mm)			Internal sizes (mm)			Weight (kg)	Fire resistance (mins.)
	H	L	P	H	L	P		
AISM0125 K/E	420	352	433	224	157	206	45	60
AISM0530 K/E	522	404	440	314	197	201	65	60
AISM0070 K/E	695	500	500	419	277	231	120	90

Internal capacity						
Model	4mm DAT	8mm AIT	CD	DLT	LTO/Ultrium	3590Cartridge
AISM0125	74	33	30	16	22	12
AISM0530	150	54	53	20	36	22
AISM0070	312	168	111	62	96	64

FIRE-RESISTANT CABINETS FOR MAGNETIC STORAGE MEDIA

Technical features:

- High fire protection: 120-minute resistance in fire exposure conditions at a temperature of about 1010°C.
- Additional internal safe, made of melamine panels and of specific protections, with thermal insulating function.
- The seals of the internal safe and the grooves of the external door assure tightness to liquids, air, vapour and smoke.
- Protection against magnetic fields and electrostatic phenomena.

Available in two versions:

- High security EN 1300 certified lock, with dual key.
- Electronic lock with millions of possible combinations.
- Internal pullout drawers on telescopic rails, provided with internal adjustable dividers.
- Internal adjustable shelves.
- Wheels and wheel-covering profiles.

Fire-resistant cabinets for magnetic storage media								
Model	External sizes (mm)			Internal sizes (mm)			Weight (kg)	Fire resistance (mins.)
	H	L	P	H	L	P		
AISM0825 K/E	830	690	720	489	402	406	260	120
AISM0120 K/E	1220	690	720	879	402	406	350	120
AISM0130 K/E	1445	690	720	1104	402	406	480	120
AISM0635* K/E	1745	1200	720	1404	402x2	406	760	120

** 2-door version*

Internal capacity (only drawers)						
Model	4mm DAT	8mm AIT	CD	DLT	LTO/Ultrium	3590Cartridge
AISM0825	232	114	188	84	114	96
AISM0120	464	228	376	168	228	192
AISM0130	580	285	470	225	285	240
AISM0635	1160	570	940	420	570	480