



Casse continue e ATM

Cassarapida Lobby

La cassaforte da lobby per sistema di versamento motorizzato è disponibile con corazzatura derivata dalla serie RA 2012 o Parmula/UNO.

Caratteristiche prodotto:

- Versamento a bocca motorizzata
 - Consolle di comando con tastiera 16 tasti + display 16 caratteri – 2 righe, più touch-key (chiave Dallas).
 - Alimentatore integrato per funzionamento in modalità autonoma o in abbinamento ad ATM.
 - Gestione elettronica con due aree di memoria indipendenti per eventi e versamenti.
 - Rilascio scontrino di versamento (optional – con stampante).
 - Scheda di connessione per rete Ethernet (optional).
- NB: necessita applicativo SW Parma per sistemi Windows – da richiedere
- Dispositivo guida DSS per alloggiamento sacco raccolta denaro H.700mm (optional).



Possibilità di versamento a mezzo:

- contenitori H25xL130xP190 mm
- contenitori H55xL130xP190 mm

Dotazione disponibile di serie:

- buste

Armadietto copricongegni:

- n. 10 chiavi Dallas verdi (Cliente)
- n. 1 chiave Dallas nera (Master)
- n. 1 chiave Dallas blu (visualizzatore)

Lobby					
Codice	Modello	Dimensioni Esterne (mm)			Peso (kg)
		H.	L.	P.	
CRML 1417	LOBBY KBC3	1400	570	570+70	480
CRPC 1417	LOBBY KBC3 - CEN 1	1400	570	570+70	530



Supplementi	
000611041	Chiave Dallas verde aggiuntiva
009750128	Stampante
KTCR0000	Scheda connessione Ethernet
DSCR1417	Dispositivo guida DSS
VRSP7091	Contenitore DSS 85 Prefer sacco H.700mm ap. 90mm strombato
000666051	Contenitori ABS H. 55mm (min. 50 pz.) – cad.
000666057	Contenitori ABS H. 25mm (min. 50 pz.) – cad.
004992300	Buste (min. 50 pz.) – cad.
000632055	Zanca completa spessore mm 45-55 per ancoraggio a pavimento

Verniciatura in tinta RAL 7015 oppure RAL 7016



ATM

Lobby Safe

Lobby safe for motor-powered deposit system, available with armouring, deriving from RA 2012 o Parmula/UNO series.

Technical features:

- Control unit with 16-key keyboard + 2 lines x 16 character display, plus touch-key (Dallas key). Integrated power supply unit for standalone operation mode or combined with ATM.
- Electronic management with two independent memory areas for events and deposits.
- Release of deposit receipt (optional – with printer).
- Connector board for Ethernet network (optional). NB: It requires SW Parma application for Windows systems – upon request.
- DSS guide device for housing cash collection bag H.700mm (optional).



Possible to carry out deposits by means of:

- containers H25xW130xD190 mm
- containers H55xW130xD190 mm

Standard equipment:

- envelopes

Device-covering cabinet:

- n. 10 green Dallas keys (client)
- n. 1 black Dallas key (master)
- n. 1 blue Dallas key (display)

Lobby					
Code	Model	External size (mm)			Weight (kg)
		H.	L.	P.	
CRML 1417	LOBBY KBC3	1400	570	570+70	480
CRPC 1417	LOBBY KBC3 - CEN 1	1400	570	570+70	530



Extras	
000611041	Additional green Dallas key
009750128	Printer
KTCR0000	Ethernet connector board
DSCR1417	DSS guide device
VRSP7091	DSS container 85 Prefer bag H.700mm open 90mm bellmouth
000666051	ABS containers H. 55mm (min. 50 pieces) – each
000666057	ABS containers H. 25mm (min. 50 pieces) – each
004992300	Bags (min. 50 pieces) – each
000632055	Complete clamp width mm 45-55 for pavement anchoring

Matching paint RAL 7015 or RAL 7016